

### 300 Whisper Data

16.5" Barrel 70 Deg F

Charge	Powder	Bullet	Velocity	Energy	ES	SD
7.9	2400	168	1068	426	30	12
8.3	2400	168	1103	454	30	11
8.3	2400	190	1062	476	21	8
8.3	2400	250	994	549	60	22
8.6	2400	250	1040	601	50	18
9.2	4227	220	1006	495	89	33
9.2	4227	250	1011	568	89	24
9.3	4227	250	1039	599	116	44
9.4	4227	250	1027	586	135	35
8.1	AA#9	165	1033	391	52	23
8.5	AA#9	220	1013	501	71	27
8.8	AA#9	220	1071	560	28	14
8.5	AA#9	250	1005	561	25	11
8.8	AA#9	250	1040	601	36	12
20.2	AA1680	150	1994	1325	40	
20.2	AA1680	168	1906	1356	12	
17.9	AA1680	190	1754	1298	34	
10.3	AA1680	220	1023	511	33	15
15.6	AA1680	220	1492	1088	11	
10.3	AA1680	250	1013	570	44	20
11.4	AA1680	250	1147	731	13	4
13.9	AA1680	250	1304	900	38	
14.6	AA1680	250	1377	1011	36	
12.6	AA2015	165	1046	401	63	35
12.0	AA2015	200	1007	450	20	10
12.0	AA2015	220	1046	535	30	11
12.4	AA2015	220	1073	563	27	10
18.8	AA2015BR	150	1615	869	29	
18.8	AA2015BR	168	1672	1043	28	
17.7	AA2015BR	190	1564	1032	18	
15.6	AA2015BR	220	1429	998	25	
12.0	AA2015BR	250	1101	673	42	
20.6	H110	125	2283	1447	64	
18.0	H110	150	2014	1351	29	
18.0	H110	150	2073	1432	13	
17.2	H110	168	1958	1431	27	
15.4	H110	190	1725	1256	40	
8.7	H110	220	1003	492	84	13
8.9	H110	220	1012	500	27	
9.1	H110	220	1061	550	39	15
9.1	H110	220	1061	550	37	17
9.1	H110	220	1070	559	49	
12.5	H110	220	1412	974	47	
8.6	H110	250	980	533	15	6
8.9	H110	250	1052	615	41	15
12.0	H110	250	1376	1009	46	
18.9	RL7	150	1834	1121	54	
18.9	RL7	168	1823	1240	19	
15.4	RL7	220	1485	1078	47	
12.1	RL7	250	1211	814	44	